



IN-LINE BOTTLE JACKS

- Heat-treated extension screw allows low pick-up height adjustment and maximum lift height
- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912
- Unique cross-type forged release valve assures positive control
- A wide, rugged base provides stability and strength
- In-line pump allows for easy jack positioning under load

10128
12 Ton Capacity



10120
12 Ton Capacity

10200
20 Ton Capacity



Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension Screw	Base Size Length	Base Size Width	G.W.
10120	12 Ton	9-1/2"	18-5/8"	6"	3-1/8"	7"	4-1/4"	19 Lbs.
10128		6"	10-3/4"	3-1/8"	1-5/8"			16 Lbs.
10200	20 Ton	9-1/2"	18-5/8"	6"	3-1/8"	7-3/4"	5"	28 Lbs.
10208		6-1/2"	11-1/4"	3-1/8"	1-5/8"			23 Lbs.

SIDE PUMP BOTTLE JACKS



- Hydraulic system is protected from internal damage by a by-pass mechanism U.S. Patent No.5,946,912
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- Unique cross-type forged release valve assures positive load control
- A wide, rugged base provides stability and strength

Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension Screw	Base Size Length	Base Size Width	G.W.
10025C	2 Ton	7-1/4"	13-5/8"	4-3/8"	2"	3-3/4"	3-5/8"	7 Lbs.
10045C	4 Ton	8"	15-3/8"	5"	2-3/8"	4"	3-7/8"	9 Lbs.
10065C	6 Ton	8-5/8"	16-3/4"	5-1/8"	3"	4-1/4"	4"	12 Lbs.
10085C	8 Ton	8-7/8"	17-5/8"	6"	2-3/4"	4-3/4"	4-3/4"	14 Lbs.
10125C	12 Ton	9-1/2"	18-5/8"	6"	3-1/8"	5-1/4"	5-1/8"	18 Lbs.
10129C		6"	10-5/8"	3"	1-5/8"			14 Lbs.
10205C	20 Ton	9-1/2"	18-5/8"	6"	3-1/8"	6-1/4"	5-7/8"	27 Lbs.
10209C		6-1/2"	11-1/4"	3-1/8"	1-5/8"			21 Lbs.
10300	30 Ton	11"	18"	7"	N/A	8-1/8"	6-7/8"	55 Lbs.
10500	50 Ton	9-1/2"	13-7/8"	4-3/8"		10-7/8"	7-5/8"	107 Lbs.